

BANDING & STRAPPING

Metal Banding

HCL's Metal banding is a high quality band and buckle system, suitable for almost any sized application where superior strength is required.

PERFORMANCE	Strength	
	Temperature	
	Speed	
	Weathering	
	Chemical	
	Dynamic Range	

Applications

- Electrical
- Telecommunications
- Sign Fixing
- General Industry



Materials – see section 10.3

- W3** 301 SS
- On Request**
- W4** 304 SS
- W5** 316 SS

Weathering	
Chemical	
Weathering	
Chemical	

HCL Part No		Band Width		Band Thickness mm	Max System Strength kg	Band Reel Lengths m	Buckle Box Quantity
Band	Buckle	mm	in				
MBA-1/4	MBU-1/4	6.4	¼	0.51	225	30 / 50	100
MBA-3/8	MBU-3/8	9.5	⅜	0.61	400		
MBA-1/2	MBU-1/2	12.7	½	0.75	680		
MBA-5/8	MBU-5/8	15.8	⅝		890		
MBA-3/4	MBU-3/4	19.1	¾	1090			

All weights, dimensions & quantities are subject to a 2.5% tolerance.
To add material selection to the HCL Part No: for W3, add "W3".

Installation Tools – see section 9.1



MT-MB-01